

TECHNICAL PRODUCT DATA SHEET

141 RECYCLED RUBBER WALKBOARD PADS**PRODUCT DESCRIPTION**

Product Use: Malarkey Roofing Products™ (Malarkey) 141 Recycled Rubber Walkboard Pads are used as walk pad for traffic areas on the roof to protect the roof from traffic; i.e. around the hatch, around rooftop units, and walk ways to the units.

Composition and Materials: 141 Recycled Rubber Walkboard Pads are made from recycled rubber (100% of the rubber is recycled, tires and binders).

Application Standards: Approval for use on all Malarkey roofs.

TECHNICAL DATA

Typical average properties, 32" x 36" pad:

Weight	16 lbs.
Dimensions	32" x 36"
Thickness	3/8"
Color	Black

Electrostatic Propensity:AATCC
Compression & Recovery

Test Method

NEG 0.9 KV Maximum Voltage
Immediate 98.1%
After 24 Hours 99.2%
After 96 Hours 99.7%

APPLICATION PROCEDURES

Malarkey 141 Recycled Rubber Walkboard Pads may be installed by spot adhering in with a One-Part Polyurethane adhesive; i.e. ChemRex CX-948, Sikaflex-1A or Chem Link M-1. (Adhere 4 corners and one spot in center. Spots of adhesive should be at least silver dollar size). **Do not use asphalt cut-back adhesives.** Contact Malarkey for details.

TECHNICAL SERVICES

Malarkey has technical services assistance available for all phases of built-up roof coverings and requirements. Contact Malarkey for details at (800) 545-1191 or (503) 283-1191; Weekdays 7:00 a.m. to 5:00 p.m. Pacific Time.

AVAILABILITY

Malarkey 141 walkboard is available throughout North America and Pacific Rim countries. Visit www.MalarkeyRoofing.com for additional product information and availability.

Effective 12.07 | Supersedes all previously published data.

For most current version, go to www.MalarkeyRoofing.com