

TECHNICAL PRODUCT DATA SHEET
703 PLASTIC ROOF CEMENT

PRODUCT DESCRIPTION

Product Use: Malarkey Roofing Products™ (Malarkey) 703 Plastic Roof Cement is a waterproof and weather-resistant asphalt base non-asbestos premium grade fibered mastic for use on dry exterior surfaces. For repair and prevention of roof leaks and for sealing cracks around chimneys, pipes, vents, flashings, gutters and metal on flat or vertical surfaces. Resists cracking in cold weather and running in hot weather. Complies with ASTM D 4586-93 Type I.

TECHNICAL DATA

Base	Air-blown asphalt, non-asbestos fibers and fillers and petroleum solvents
Color	Black
Non-Volatile Content	70% minimum
Consistency	Trowel grade
SETA Flash Point	Approximately 120° F (49° C)
Maximum VOC	300 grams/liter
Container Sizes	5 gallon (19 L)

APPLICATION PROCEDURE

Malarkey 703 Plastic Roof Cement is ready to use. Apply with a trowel or putty knife. Apply pressure with the applicator to increase adhesion. Imbed glass or cotton fabric between two layers of cement for increased service life. In cold temperatures, store the container in a warm room. Clean tools with mineral spirits.

TECHNICAL SERVICES

Malarkey has technical assistance available for all phases of built-up roof coverings and requirements. Contact Malarkey for details at (800) 545-1191 or (503) 283-1191; Weekdays 7:00 a.m. to 5:00 p.m. Pacific Time.

AVAILABILITY

Malarkey 703 Plastic Roof Cement is available throughout North America and Pacific Rim countries. Visit www.MalarkeyRoofing.com for additional product information and availability.

Effective 12.07 | Supersedes all previously published data.

For most current version, go to www.MalarkeyRoofing.com