



TECHNICAL PRODUCT DATA SHEET

RECYCLED RUBBER WALKBOARD PADS

141

PRODUCT DESCRIPTION

Product Use: Malarkey Roofing Products (Malarkey) Recycled Rubber Walkboard Pads 141 are used as walk pads for traffic areas on the roof to protect the roof from traffic, i.e. around the hatch, rooftops units, and ways to the units.

Composition and Materials: Recycled Rubber Walkboard Pads 141 are made from recycled rubber (100% of the rubber is recycled tires and binders).

Application Standards: Approval for use on all Malarkey roofs.

TECHNICAL DATA

Typical properties, 32" x 36" pad:

Weight	16 lbs.
Dimensions	32" x 36"
Thickness	3/8"
Color	Black

Electrostatic Propensity - AATCC Test Method: NEG 0.9 KV Maximum Voltage
Compression & Recovery

Immediate	98.1%
After 24 Hours	99.2%
After 96 Hours	99.7%

APPLICATION PROCEDURES

Malarkey Recycled Rubber Walkboard Pads 141 may be installed by spot adhering in with a One-Part Polyurethane adhesive: i.e. ChemRex CX-948, Sikaflex-1-A or Hem Link M-1. (Adhere 4 corners and one spot in center. Spots of adhesive should be at least silver dollar size.) Do not use asphalt cut-back adhesives. Contact Malarkey for details.

TECHNICAL SERVICES

Malarkey has technical assistance available for all phases and requirements of built-up roof coverings. Contact Malarkey for details at (800) 545-1191 or (503) 283-1191, weekdays 7:00 a.m. to 5:00 p.m. Pacific Time.

AVAILABILITY

Malarkey 141 Walkboard is available throughout North America and Pacific Rim countries. Visit www.MalarkeyRoofing.com for additional product information and availability.

Effective 10.09 | Supersedes all previously published data.

For most current version, go to www.MalarkeyRoofing.com