



## TECHNICAL PRODUCT DATA SHEET

### 501 MODIFIED BASE

#### **PRODUCT DESCRIPTION**

**Product Use:** Malarkey Roofing Products™ (Malarkey) 501 Modified Base is suitable for use as a base sheet for hot asphalt, cold process and torch applications. This high-performance base sheet may be used over various combustible and non-combustible decks as the initial ply or multiple interplies for a specified roof system. Please consult Malarkey for approval of roof systems.

**Precautions:** Malarkey 501 Modified Base requires dry storage and protection from the weather. Do not apply wet base sheet. Roof decks should be sound, dry, smooth, meet necessary local requirements and provide positive drainage.

**Composition and Materials:** Malarkey 501 Modified Base is manufactured on tested Malarkey fiberglass mat impregnated and coated with an SBS modified asphalt and lightly surfaced with a mineral release material.

**Application Standards:** Approval for use on all fire-rated roofs. See Malarkey manual for specified information. Contains the asphalt equivalent of Type G2 base sheet and may be used where a quality base sheet is specified.

#### **TECHNICAL DATA**

Typical average properties, 3 sq. roll:

Weight/square	30.5 lbs. (14 kg)
Weight/roll	92 lbs. (41.8 kg)
Dimensions	39-3/8" wide x 99' long (1 m x 30.2 m)
Thickness	45 mils
Lay lines	2", 12-1/2" and 18-3/4" minimum (50.8 mm, 317.5 mm, 476.2 mm)

Meets or exceeds ASTM D 4601-98 Type II. Complies with and listed by UL, FM and WH.

#### **APPLICATION PROCEDURE**

Malarkey 501 Modified Base shall be applied as specified in the Malarkey Specification Manual. It may be applied in cold weather. Please follow cold weather application and general requirements.

#### **WARRANTIES**

Malarkey offers various warranties to meet specific requirements. The warranty package includes 5,10,15 and 20-year limited and unlimited coverage. Contact Malarkey for full details.

#### **TECHNICAL SERVICES**

Malarkey has technical services assistance available for all phases of built-up roof coverings and requirements. Contact Malarkey for details at (800) 545-1191 or (503) 283-1191; Weekdays 7:00 a.m. to 5:00 p.m. Pacific Time.

#### **AVAILABILITY**

Malarkey 501 Modified Base is available throughout North America and Pacific Rim countries. Visit [www.MalarkeyRoofing.com](http://www.MalarkeyRoofing.com) for additional product information and availability.