



Plastic Roof Cement

Material Safety Data Sheet

Last updated: 02-08-2008

SECTION 1 - PRODUCT & COMPANY IDENTIFICATION

Name: **Plastic Roof Cement**
 Product Number: **703**
 Class: **Asphalt Cutback Heavy Paste**
 Company Address: 3131 N. Columbia Blvd., Portland, OR 97217-7472 • P.O. Box 17217, Portland, OR 97217-0217
 Telephone: (503) 283-1191 • 1-800-545-1191 Fax: (503) 289-7644 Website: <http://www.malarkey-rfg.com>

SECTION 2 - HAZARDOUS INGREDIENTS

CAS# 64742-88-7 %Volume: 15-20%

Weight per Gallon: Approx. 9.0 lbs
 %Volatile Volume: 42-49%,
 %Water Volume: 0.0%

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview: This product contains asphalt. Some asphalt contains sulfur compounds which may form H₂S when heated or burnt.
Potential Health Effects:
Skin: May cause skin irritation.
Eyes: May cause eye irritation.
Ingestion: NDA
Inhalation (Primary route of exposure): Vapors above TLV may asphyxiate.

SECTION 10 - STABILITY & REACTIVITY

Chemical Stability: Stable under normal condition
Conditions to Avoid: Source of ignition
Incompatible Materials: Strong Oxidants
Hazardous Decomposition Products: May form CO_x, black particulates
Hazardous Polymerization: Will not occur

SECTION 4 - FIRST AID MEASURES

Eye: Wash eyes with water thoroughly for 15 minutes.
Skin: Wash Skin with soap and water.
Ingestion: Ingestion is not considered a potential route of exposure
Inhalation: Move person to fresh air. Apply artificial respiration if needed.
 Call a physician

SECTION 11 - TOXICOLOGICAL INFORMATION

Acute Toxicity: NDA
Carcinogenicity: The IARC Monographs (Vol. 35) reporting on mice painting studies states that there is sufficient evidence for the carcinogen in experimental animals of extracts of some asphalts. The same document states that there is inadequate evidence that asphalts alone are carcinogenic to humans.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: 105°F
Qualitative Flammable & Reactivity Properties: Flammable
Suitable Extinguishing Media: CO₂, Dry Chem foam
Unusual Fire & Explosion Hazard: Liquid Asphalt, H₂S may be present.
Guidance to Fire Fighters: N/A
PPE & Precautions for Fire Fighters: Use proper PPE

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: None

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Clean Up Techniques: Extinguish all sources of ignition. Absorb the material with clay.
Personal Precautions: See Section 8

SECTION 13 - DISPOSAL CONSIDERATION

Contact the local authority, comply with local code

SECTION 7 - HANDLING & STORAGE

Handling & Storage: Keep storage container closed. Avoid flames & flammable material

SECTION 14 - TRANSPORT INFORMATION

Shipping Name: Combustible Liquid, NOS (contain mineral spirits), **labeling:** Not Required
Hazard Class: Combustible
DOT: Regulated, I.M.C.O>: UN (NA), #1993 Class: 3.3

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines: Exposure Limit Values: TLV- 500ppm PEL: 500ppm
Engineering Controls: Do not store near flame. Use in well ventilated areas
PPE:
Eye: Recommended but not required
Skin: Neoprene gloves are recommended. Wear apron.
Respiratory: Not normally required
General Hygiene Considerations: Washing facility recommended

SECTION 15 - REGULATORY INFORMATION

All Components of this products are on the TSCA inventory or are exempt from TSCA inventory requirements under 40 CFR 720.30

SECTION 16 - OTHER INFORMATION

HMIS Rating:
Health: 2 **Flammability:** 2 **Reactivity:** 0 **PPE:** A

Note: PPE: Personal Protective Equipment
 N/A: Not Applicable, NDA: No Data Available

Disclaimer:

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Malarkey Roofing Products. The data on this sheet are related only to the specific material designated herein. Malarkey Roofing Products assumes no legal responsibility for use or reliance upon these data.

SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES

Boiling Range: 310-400°F minimum
Maximum V.O.C.: 300g/liter
Vapor Pressure: 7mm @ 100°F
Vapor Density: Heavier than Air
Evaporation Rate: Slower than Ether
Explosive Limits: LEL: 1%, UEL: NDA