



TECHNICAL PRODUCT DATA SHEET

706 ASPHALT PRIMER

PRODUCT DESCRIPTION

Product Use: Malarkey Roofing Products™ (Malarkey) 706 Asphalt Primer is designed as a prime coat for concrete, metal, composition roofing or any non-asphaltic surfaces. Assists in adhesion of all asphalt products to masonry, metals or asphaltic surfaces. Complies with ASTM D 41-94.

TECHNICAL DATA

Base	Selected, specially blown asphalt and petroleum solvents
Consistency	Light-bodied liquid suitable for brushing, rolling or spraying
Weight Per Gallon	Approximately 7.0 lbs. (3.2 Kg)
Solids Content	40% by weight minimum
SETA Flash Point	Approximately 117° F (47° C)
Coverage	0.5 to 1.0 gallons (1.9 L to 3.8 L) per square
Maximum VOC	500 grams/liter
Container Sizes	5 gallon (19 L) 55 gallon (208 L)

APPLICATION PROCEDURE

Malarkey 706 Asphalt Primer is ready to use. Do not thin. Standard coverage is approximately 100 square feet per gallon on concrete, roofing and roofing felt; 200 square feet per gallon over metal. Apply with a brush, roller or spray equipment.

TECHNICAL SERVICES

Malarkey has technical assistance available for all phases of built-up roof coverings and requirements. Contact Malarkey for details at (800) 545-1191 or (503) 283-1191; Weekdays 7:00 a.m. to 5:00 p.m. Pacific Time.

AVAILABILITY

Malarkey 706 Asphalt Primer is available throughout North America and Pacific Rim countries. Visit www.MalarkeyRoofing.com for additional product information and availability.

Effective 12.07 | Supersedes all previously published data.

For most current version, go to www.MalarkeyRoofing.com