



TECHNICAL PRODUCT DATA SHEET

#707 (Low VOC) ASPHALT PRIMER

PRODUCT DESCRIPTION

Product Use: Malarkey Roofing Products (Malarkey) #707 Asphalt Primer is designed as a prime coat for concrete, metal, composition roofing or any non-asphaltic surfaces. Assists in adhesion of all asphalt products to masonry, metals or other asphaltic surfaces. Complies with ASTM D 41-94.

TECHNICAL DATA

| | |
|-------------------|--|
| Base | Selected, specially blown asphalt and petroleum solvents |
| Consistency | Light-bodied liquid suitable for brushing, rolling or spraying |
| Weight Per Gallon | Approximately 7.5 lbs. (3.4 Kg) |
| Solids Content | >50% by weight minimum |
| SETA Flash Point | Approximately 110 ° F (43 ° C) |
| Coverage | 0.75 to 1.0 gal. (.34 to .45 L) per square |
| Maximum VOC | <350 grams/liter |
| Container Sizes | 5 gallon 55 gallon |

APPLICATION PROCEDURE

Malarkey #707 Asphalt Primer is ready to use. Do not thin. Standard coverage is approximately 100 square feet per gallon on concrete, roofing and roofing felt, 200 square feet per gallon over metal. Apply with a brush, roller or spray equipment.

TECHNICAL SERVICES

Malarkey has technical assistance available for all phases of built-up roof coverings and requirements. Contact Malarkey for details at (800) 545-1191 or (503) 283-1191; Weekdays 7:00 a.m. to 5:00 p.m. Pacific Time.

AVAILABILITY

Malarkey #707 Asphalt Primer is available throughout North America and Pacific Rim countries. Visit www.MalarkeyRoofing.com for additional product information and availability.

Effective 06.07 Supersedes all previously published data