



Malarkey
Roofing ProductsTM

PRODUCT

DATA GUIDE

United States

Malarkey Shingle Color Availability by Region:

Portland Color Availability	Antique Brown	Black Oak	Heather	Midnight Black	Natural Wood	Oxford Grey	Rainforest	Sienna Blend	Silverwood	Storm Grey	Weathered Wood
Legacy®	☘			☘	☘	☘	☘	☘	☘	☘	☘
Legacy AB®	☘	☘		☘	☘	☘	☘	☘	☘	☘	☘
Northwest XL™	☘	☘		☘	☘	☘		☘	☘	☘	☘
Northwest XL AB™	☘	☘		☘	☘			☘	☘	☘	☘
Highlander-CS™	☘	☘	☘	☘	☘	☘		☘	☘	☘	☘
Highlander-CS AR™	☘	☘		☘	☘	☘		☘	☘	☘	☘
Alaskan® / Hurricane™	☘	☘		☘	☘	☘	☘	☘	☘	☘	☘
Duraseal™ 25	☘	☘		☘	☘	☘		☘	☘	☘	☘

For Ecoasis and Ecoasis Premium color availability, please see page 4.

South Gate Color Availability	Antique Brown	Dove White	Golden Brown	Midnight Black	Natural Wood	Oxford Grey	Pastel Green	Rainforest	Rustic Slate	Sandstone	Sienna Blend	Silverwood	Storm Grey	Terra Corta	Weathered Wood
Legacy®	☘			☘	☘	☘		☘			☘	☘	☘		☘
Northwest XL™	☘			☘	☘				☘	☘	☘	☘	☘	☘	☘
Highlander-CS™	☘	☘		☘	☘			☘	☘	☘	☘	☘	☘	☘	☘
Alaskan® / Hurricane™	☘			☘		☘		☘			☘	☘			☘
Duraseal™ 20	☘	☘	☘	☘		☘	☘	☘			☘	☘			☘

PRODUCTS

SHINGLES	2-4
HIP & RIDGE	5
UNDERLAYMENT	5
SELF ADHERED UNDERLAYMENT	6
FIBERGLASS BUILT-UP ROLLED ROOFING	6
CEC TITLE 24 BRIGHT WHITE REFLECTIVE CAP SHEETS	6
CONVENTIONAL BASE SHEETS	6
CONVENTIONAL PLY SHEETS	6
CONVENTIONAL CAP SHEETS	7
SBS MODIFIED BASE & PLY SHEETS	7
SBS MODIFIED CAP SHEETS	8
SELF ADHERED RESIDENTIAL PRODUCTS	8
APP MODIFIED BASE & CAP SHEETS	9
WALKBOARD	10
SEBS ROOFING ASPHALT	10
ROOF COATINGS & ADHESIVES	10-11

STOCK ITEMS AND COLORS

Stock items and colors are normally available from our inventories for immediate shipment.

** SPECIAL ORDER ITEMS AND COLORS **

A minimum of 600 squares per run, with the customer taking all overruns up to 10% of original order quantity with a \$600 special color run charge per production run. If a product features **Scotchgard Algae Resistant Roofing System from 3M** there will be an additional charge. Allow 6 weeks for special orders to be processed.

Please contact your local Malarkey Sales Representative for additional details.

FOR ADDITIONAL INFORMATION call or write:

[Malarkey Roofing Products](http://www.MalarkeyRoofing.com)

P.O. Box 17217

Portland, OR 97217

(503) 283-1191 or (800) 545-1191

Facsimile (503) 289-7644

Website: www.MalarkeyRoofing.com

Typical office hours: 8 am - 5 pm Pacific time

Order Desk

(503) 283-0182 or (800) 545-0182

Facsimile (503) 283-8069

Technical Services

(503) 283-1191 or (800) 545-1191

Facsimile (503) 283-5405






This information is effective March 8, 2010 and supersedes all previously published data. Malarkey Roofing Products reserves the right to change any information contained herein without notice.

For the most current version of all product literature go to www.MalarkeyRoofing.com


3-Tab Shingles



PRODUCT DESCRIPTION	TESTING & APPROVALS	SPECIFICATIONS
<p>202 Dura-Seal™ 20-year Classic 3-Tab Metric Fiberglass Shingle 20-Year Limited Warranty 54 mph (87 kph) Limited Wind Warranty</p>	<p>ASTM D7158 Class H ASTM D3018 Type I ASTM E108 Class A</p>	<p>Appr. Wt./Sq.: 200 lbs. (90.7 kg) Shingles/Sq.: 66 Bundles/Sq.: 3 Exposure: 5⁵/₈" (142.9 mm) Squares/Pallet: 16 South Gate (SG)</p> <p>Please consult Malarkey Color Chart inside cover page for Regional Color Availability</p>
<p>204 Dura-Seal™ 25-year Classic 3-Tab Metric Fiberglass Shingle 25-Year Limited Warranty 54 mph (87 kph) Limited Wind Warranty</p>	<p>ASTM D7158 Class H ASTM D3462 ASTM D3018 Type I ASTM E108 Class A CSA A123.1/A123.5</p>	<p>Appr. Wt./Sq.: 235 lbs. (106.6 kg) Shingles/Sq.: 66 Bundles/Sq.: 3 Exposure: 5⁵/₈" (142.9 mm) Squares/Pallet: 16 Portland (PDX)/SG</p> <p>Please consult Malarkey Color Chart inside cover page for Regional Color Availability</p>
<p>230 The Alaskan® 35-year SBS Modified Classic 3-Tab Metric Shingle 35-Year Limited Warranty 100 mph Limited (161 kph) Wind Warranty</p>	<p>ASTM D3462 ASTM D3161 Class F ASTM D3018 Type I ASTM E108 Class A UL 2218 Class 4 Impact Resistant CSA A123.1/A123.5</p>	<p>Appr. Wt./Sq.: 235 lbs. (106.6 kg) Shingles/Sq.: 66 Bundles/Sq.: 3 Exposure: 5⁵/₈" (142.9 mm) Squares/Pallet: 16 PDX/SG</p> <p>Please consult Malarkey Color Chart inside cover page for Regional Color Availability</p>
<p>240 Hurricane™ 35-year SBS Modified Classic 3-Tab Metric Shingle Featuring the Scotchgard™ Algae Resistant Roofing System from 3M* 35-Year Limited Warranty 100 mph Limited (161 kph) Wind Warranty</p> <p>*20-year algae resistance warranty</p>	<p>ASTM D3462 ASTM D3161 Class F ASTM D3018 Type I ASTM E108 Class A UL 2218 Class 4 Impact Resistant CSA A123.1/A123.5</p> 	<p>Appr. Wt./Sq.: 235 lbs. (106.6 kg) Shingles/Sq.: 66 Bundles/Sq.: 3 Exposure: 5⁵/₈" (142.9 mm) Squares/Pallet: 16 PDX/SG</p> <p>Please consult Malarkey Color Chart inside cover page for Regional Color Availability</p>

Laminated Shingles

PRODUCT DESCRIPTION	TESTING & APPROVALS	SPECIFICATIONS
<p>271 Highlander-CS 30-year- Laminated Shingle</p> <p>Featuring the Patented Malarkey Zone</p>  <p>277...Highlander-CS AR 30-year, Featuring Algae Resistant Granules*</p> <p>30-Year Limited Product Warranty 70 mph Limited (113 kph) Wind Warranty *10-year algae resistance warranty</p>	<p>ASTM D7158, Class H ASTM D 3462 ASTM D3018 Type I ASTM E108 Class A CSA A123.1/A123.5</p>	<p>Appr. Wt./Sq.: 245 lbs. (111 kg) Shingles/Sq.: 64 Bundles/Sq.: 4 Exposure: 5⁵/₈" (142.9 mm) Squares/Pallet: 12 PDX/SG</p> <p>Please consult Malarkey Color Chart inside cover page for Regional Color Availability</p>
<p>270 Northwest XL 40-year Laminated Shingle</p> <p>Featuring the Patented Malarkey Zone</p>  <p>269 Northwest XL AB 40-year, Featuring the Scotchgard Algae Resistant Roofing System from 3M*</p> <p>40-Year Limited Product Warranty 80 mph Limited (129 kph) Wind Warranty *20-year algae resistance warranty</p> 	<p>ASTM D7158, Class H ASTM D 3462 ASTM D3161 Class F ASTM D3018 Type I ASTM E108 Class A CSA A123.1/A123.5</p>	<p>Appr. Wt./Sq.: 260 lbs. (117.9 kg) Shingles/Sq.: 64 Bundles/Sq.: 4 Exposure: 5⁵/₈" (142.9 mm) Squares/Pallet: 12 PDX/SG</p> <p>Please consult Malarkey Color Chart inside cover page for Regional Color Availability</p>
<p>272 Legacy 50-year SBS Modified Laminated Shingle</p> <p>Featuring the Patented Malarkey Zone</p>  <p>273 Legacy AB 50-year, Featuring the Scotchgard Algae Resistant Roofing System from 3M*</p> <p>50-Year Limited Product Warranty 110 mph (177 kph) Limited Wind Warranty *20-year algae resistance warranty</p> 	<p>ASTM D3462 ASTM D3161 Class F ASTM D3018 Type I ASTM E108 Class A UL 2218 Class 4 Impact Resistant CSA A123.1/A123.5</p>	<p>Appr. Wt./Sq.: 275 lbs. (124.8 kg) Shingles/Sq.: 64 Bundles/Sq.: 4 Exposure: 5⁵/₈" (142.9 mm) Squares/Pallet: 12 PDX/SG</p> <p>Please consult Malarkey Color Chart inside cover page for Regional Color Availability</p>

Laminated Reflective Shingles

PRODUCT DESCRIPTION	TESTING & APPROVALS	SPECIFICATIONS														
<p>280 Ecoasis™</p> <p>40-year Reflective Laminated Shingle</p> <p>Featuring the Patented Malarkey Zone®</p>  <p>40-Year Limited Product Warranty 80 mph Limited (129 kph) Wind Warranty Listed with CRRC as a reflective shingle Meets CEC Title 24 Part 6 Energy Standards</p>	<p>ASTM D7158, Class H ASTM D 3462 ASTM D3161 Class F ASTM D3018 Type I ASTM E108 Class A CSA A123.1/A123.5</p>	<p>Apr. Wt./Sq.: 260 lbs. (117.9 kg) Shingles/Sq.: 64 Bundles/Sq.: 4 Exposure: 5⁵/₈" (142.9 mm) Squares/Pallet: 12 SG</p> <p>Color Availability: Adobe, Agave, Desert Jewel, Desert White, Mesquite, Tumbleweed</p> <table border="1"> <thead> <tr> <th>Ecoasis</th> <th>Hip and Ridge</th> </tr> </thead> <tbody> <tr> <td>Adobe</td> <td>Desert Tan</td> </tr> <tr> <td>Agave</td> <td>Silverwood</td> </tr> <tr> <td>Desert Jewel</td> <td>Sandstone</td> </tr> <tr> <td>Desert White</td> <td>Dove White</td> </tr> <tr> <td>Mesquite</td> <td>Cedar</td> </tr> <tr> <td>Tumbleweed</td> <td>Tumbleweed</td> </tr> </tbody> </table> <p style="text-align: center;">CORRESPONDING COLOR - ECOASIS™ AND HIP AND RIDGE SHINGLES</p>	Ecoasis	Hip and Ridge	Adobe	Desert Tan	Agave	Silverwood	Desert Jewel	Sandstone	Desert White	Dove White	Mesquite	Cedar	Tumbleweed	Tumbleweed
Ecoasis	Hip and Ridge															
Adobe	Desert Tan															
Agave	Silverwood															
Desert Jewel	Sandstone															
Desert White	Dove White															
Mesquite	Cedar															
Tumbleweed	Tumbleweed															

<p>283 Ecoasis Premium™</p> <p>50-year SBS Modified Reflective Laminated Shingle</p> <p>Featuring the Patented Malarkey Zone®</p>  <p>Featuring the Scotchgard™ Algae Resistant Roofing System from 3M*</p> <p>50-Year Limited Product Warranty 110 mph (177 kph) Limited Wind Warranty *20-year algae Resistance Warranty Listed with CRRC as a reflective shingle Meets CEC Title 24 Part 6 Energy Standards</p>	<p>ASTM D3462 ASTM D3161 Type I Class F ASTM D3018 Type I ASTM E108 Class A UL 2218 Class 4 Impact Resistant CSA A123.1/A123.5</p> 	<p>Apr. Wt./Sq.: 275 lbs. (124.8 kg) Shingles/Sq.: 64 Bundles/Sq.: 4 Exposure: 5⁵/₈" (142.9 mm) Squares/Pallet: 12 South Gate</p> <p>Color Availability: Agave, Mesquite, Tumbleweed</p> <p>Coordinating Hip & Ridge: 283 Ecoasis Premium MUST USE: 225 Hip & Ridge Strips AB</p>
---	--	--

<i>Ecoasis Color Name</i>	<i>CRRC Initial Solar Reflectance</i>	<i>CRRC Initial Thermal Emittance</i>	<i>Solar Reflective Index</i>
Adobe	.28	.91	30
Agave	.25	.92	26
Desert Jewel	.28	.90	29
Desert White	.26	.91	27
Mesquite	.28	.89	29
Tumbleweed	.26	.91	27
<i>Ecoasis Premium Name</i>	<i>CRRC Initial Solar Reflectance</i>	<i>CRRC Initial Thermal Emittance</i>	<i>Solar Reflective Index</i>
Agave	.27	.92	29
Mesquite	.28	.93	31
Tumbleweed	.26	.93	28

Matching Hip and Ridge Shingles

PRODUCT DESCRIPTION	SPECIFICATIONS	COLORS	
222 EZ-Ridge™ 8" High Profile Decorative Ridge Shingle with Seal Down	Appr. Wt./Bundle: 40 lbs. (18.14 kg) Shingles/Box: 30 Ln. Ft. Coverage: 20' (6.562 m) Exposure: 8 ¹ / ₄ " (209 mm) 8" Wide (203 mm) Boxes/Pallet: 42 SG	Antique Brown Autumn Blend Bark Wood Birchwood Black Oak Blue Slate Burnt Wood Cedar/Mesquite Desert Tan/Adobe Dove White/ Desert White Golden Brown Midnight Black Mission Brown	Natural Wood Oxford Grey Pewter Rainforest Rustic Slate Sandstone Desert Jewel Shadow Grey Sienna Blend Silverwood/Agave Storm Grey Terra Cotta Tumbleweed Weathered Wood
224 EZ-Ridge XT™ 10" High Profile Decorative Ridge Shingle with Seal Down	Appr. Wt./Box: 50 lbs. (22.68 kg) Shingles/Box: 30 Ln. Ft. Coverage: 20' (6.6 m) Exposure: 8 ¹ / ₄ " (209 mm) 10" Wide (254 mm) Boxes/Pallet: 42 PDX/SG	Antique Brown Mesquite Midnight Black Natural Wood Oxford Grey Rainforest Sienna Blend Silverwood/Agave	Storm Grey Tumbleweed Weathered Wood
225 Hip & Ridge Strips AB SBS Modified Ridge Strips Featuring the Scotchgard™ Algae Re- sistant Roofing System from 3M* * If a 20-year algae resistance warranty is de- sired, shingles and Hip & Ridge Strips featuring the Scotchgard Algae Resistant Roofing System from 3M are required.	Appr. Wt./Bundle: 70 lbs. (31.8 kg) Units/Bundle: 88 Shingles/Bundle: 22 Ln. Ft. Coverage: 41' 3" (12.6 m) Exposure: 5 ⁵ / ₈ " (143 mm) Scored Strip Provides 13 ¹ / ₄ " tall x 9 ⁷ / ₈ " wide Unit with Seal Down for 5 5/8" exposure Bundles/Pallet: 60 PDX	Antique Brown Mesquite Midnight Black Natural Wood Oxford Grey Rainforest Sienna Blend Silverwood/Agave	Storm Grey Tumbleweed Weathered Wood
226 Hip & Ridge Strips SBS Modified Ridge Strip	Appr. Wt./Bundle: 70 lbs. (31.8 kg) Units/Bundle: 88 Shingles/Bundle: 22 Ln. Ft. Coverage: 41' 3" (12.6 m) Exposure: 5 ⁵ / ₈ " (143 mm) Scored Strip Provides 13 ¹ / ₄ " tall x 9 ⁷ / ₈ " wide Unit with Seal Down for 5 5/8" exposure Bundles/Pallet: 60 SG	Antique Brown Dove White Midnight Black Natural Wood Oxford Grey Rainforest Rustic Slate	Sandstone Sienna Blend Silverwood Storm Grey Weathered Wood
227 12" Hip & Ridge Strips AB Featuring the Scotchgard™ Algae Resis- tant Roofing System from 3M* *20-year algae resistance warranty; Required when using shingles featuring Scotchgard	Appr. Wt./Bundle: 70 lbs. (31.8 kg) Units/Bundle: 66 Shingles/Bundle: 22 Ln. Ft. Coverage: 30' 11" (9.43 m) Exposure: 5 ⁵ / ₈ " (143 mm) Scored Strip Provides 13 ¹ / ₄ " tall x 12" wide Unit with Seal Down for 5 5/8" exposure Bundles/Pallet: 60 PDX	See above for available colors in 225 (Mesquite and Tumblewood unavailable)	



Underlayment - Universal Steep Slope Underlayment

PRODUCT DESCRIPTION & TESTING INFORMATION	SPECIFICATIONS	SURFACING
Right Start UDL® SBS Modified Fiberglass Underlayment ASTM D 4601 Type II Intertek/WHI Mark-Class 'A' Fire Rated ICC-ES Report ESR-1561 Meets Requirements For: ASTM D 4869 & D 226 Type II	Appr. Wt./Roll: 75 lbs. (34.0 kg) Coverage: 2 square Width: 39 ³ / ₈ " (1 m) Length: 66' (20.1 m) Rolls/Pallet: 30 PDX/SG	Sand Parting Agent Both Sides

Self-Adhered Underlayment: Ice & Water Eave & Valley Guard

Arctic Seal 401

Self Adhered Underlayment

Appr. Wt./Roll: 77 lbs. (34.9 kg)

Sand

Coverage: 2 sq.

Width: 39³/₈" (1 m)

Length: 65' 8" (20 m)

Thickness: 70 mil

Rolls/Pallet: 20 PDX/SG

Roll Roofing

PRODUCT DESCRIPTION & TESTING INFORMATION

SPECIFICATIONS

COLORS

PRODUCT DESCRIPTION & TESTING INFORMATION	SPECIFICATIONS	COLORS
350 GR Premium SBS Modified Mineral Surfaced Fiberglass Cap Sheet <i>Meets or is listed with:</i> ASTM D 3909 Intertek/WHI Mark-Used in Class 'A' Fire Rating UL Classified as Class A Underlayment	Appr. Wt./Roll: 78 lbs. (35.4 kg) Coverage: 1 square Width: 39 ³ / ₈ " (1 m) Length: 33' (10 m) Rolls/Pallet: 30 PDX/SG	Antique Brown Red Dove White Sienna Blend Midnight Black Silverwood Natural Wood Storm Grey Oxford Grey Weathered Wood Rainforest

Fiberglass Built-Up Roofing

Title 24 Bright White Reflective Cap Sheets

PRODUCT DESCRIPTION & TESTING INFORMATION

SPECIFICATIONS

524 - RCap Plus <i>Meets or is listed with:</i> ASTM D 3909 ASTM E 108-Intertek/WHI Mark-Used in Class 'A', 'B' and C Fire Ratings CRRC listed; CEC, Title 24 Part 6 Compliant	Appr. Wt./Roll: 77 lbs. (34.9 kg) Coverage: 1 square Width: 39 ³ / ₈ " (1 m) Length: 33' (10.1 m) Rolls/Pallet: 25 PDX/SG
---	---

624 - RCap <i>Meets or is listed with:</i> ASTM D 3909 ASTM E 108-Intertek/WHI Mark-Used in Class 'A', 'B' and C Fire Ratings CRRC listed; CEC, Title 24 Part 6 Compliant	Appr. Wt./Roll: 100 lbs. (45.4 kg) Coverage: 1 square Width: 39 ³ / ₈ " (1 m) Length: 33' (10.1 m) Rolls/Pallet: 20 PDX/SG
--	--

Base Sheets - Conventional

PRODUCT DESCRIPTION & TESTING INFORMATION

SPECIFICATIONS

SURFACING

515 Base <i>Meets or is listed with:</i> ASTM D 4601 Type II, UL 55 'A' Type G2 ASTM E 108-Intertek/WHI Mark-Used in Class 'A' 'B' and 'C' Fire Rating, UL 790 Classi- fied in Class 'A', 'B', and 'C' Fire Construction FM approved	Appr. Wt./Roll: 83 lbs. (37.7 kg) Coverage: 3 square Width: 39 ³ / ₈ " (1 m) Length: 99' (30.2 m) Rolls/Pallet: 20 PDX/SG	Sand Parting Agent Both Sides
--	---	----------------------------------

Cap Sheets - Conventional

PRODUCT DESCRIPTION & TESTING INFORMATION

SPECIFICATIONS

COLORS

502 Cap <i>Meets or is listed with:</i> ASTM D 3909; UL 55 'A' Type G3 ASTM E 108-Intertek/WHI Mark-Used in Class 'A' 'B' and 'C' Fire Rating, UL 790 Classified in Class 'A', 'B', and 'C' Fire Con- struction, FM Approved	Appr. Wt./Roll: 72 lbs. (32.7 kg) Coverage: 1 square Width: 39 ³ / ₈ " (1 m) Length: 33' (10 m) Rolls/Pallet: 25 or 30 PDX, 30 SG	Dove White Midnight Black Tan
---	---	-------------------------------------

Ply Sheets - Conventional

PRODUCT DESCRIPTION & TESTING INFORMATION

500 - Ply 4

Meets or is listed with:

ASTM D 2178 Type IV, UL 55 'A' Type G1
ASTM E 108-Intertek/WHI Mark-Used in Class 'A', 'B'
and 'C' Fire Listings, UL 790 Classified in Class 'A', 'B',
and 'C' Fire Construction, FM Approved

SPECIFICATIONS

Appr. Wt./Roll: min. 36 lbs. (16.3 kg)
Coverage: 5 square
Width 39³/₈" (1 m), Length: 165' (50.3 m)
Rolls/Pallet: 30 PDX/SG
*Available in 10 square roll - 16 rolls/pallet, 72 lbs./roll**
**Southgate production only*

506 - Ply 6

Meets or is listed with:

ASTM D 2178 Type VI, UL 55 'A' Type G1
ASTM E 108-Intertek/WHI Mark-Used in Class 'A', 'B'
and 'C' Fire Listings, UL 790 Classified in Class 'A', 'B',
and 'C' Fire Construction, FM Approved

Appr. Wt./Roll: min. 42 lbs. (19.05 kg)
Coverage: 5 square
Width: 39³/₈" (1 m)
Length: 165' (50.3 m)
Rolls/Pallet: 25 PDX, 30 SG

SBS Modified Base & Ply Sheets

PRODUCT DESCRIPTION & TESTING INFORMATION

501 - Modified Base

Meets or is listed with:

ASTM D 4601, Type II; ASTM E 108-Intertek/WHI
Mark-Used in Class 'A', 'B' and 'C' Fire Listings, UL 790
Classified in Class 'A', 'B', and 'C' Fire Construction, FM
Approved

SPECIFICATIONS

Appr. Wt./Roll: 92 lbs. (41.8 kg)
Coverage: 3 square
Width: 39³/₈" (1 m)
Length: 99' (30.2 m)
Rolls/Pallet: 20 PDX/SG

SURFACING

Sand Parting Agent
Both Sides

503 - Modified Base

Meets or is listed with:

ASTM D 4601, Type II; ASTM E 108-Intertek/WHI
Mark-Used in Class 'A', 'B' and 'C' Fire Listings, UL 790
Classified in Class 'A', 'B', and 'C' Fire Construction, FM
Approved

Appr. Wt./Roll: 70 lbs. (31.7 kg)
Coverage: 2 square
Width: 39³/₈" (1 m)
Length: 66' (20.1 m)
Rolls/Pallet: 28 PDX, 30 SG

Sand Parting Agent
Both Sides

602 - Arctic Shield Modified Base

Meets or is listed with:

ASTM D 4601, Type II; ASTM E 108-Intertek/WHI
Mark-Used in Class 'A', 'B' and 'C' Fire Listings, UL 790
Classified in Class 'A', 'B', and 'C' Fire Construction, FM
Approved

Appr. Wt./Roll: 95 lbs. (43.1 kg)
Coverage: 2 square
Width: 39³/₈" (1 m)
Length: 66' (20.1 m)
Rolls/Pallet: 20 PDX/SG

Sand Parting Agent
Both Sides

603 - Modified Superbase

Meets or is listed with:

ASTM D 4601, Type II, ASTM D 6163 Type I
ASTM E 108-Intertek/WHI Mark-Used in Class 'A', 'B'
and 'C' Fire Listings, FM Approved

Appr. Wt./Roll: 75 lbs. (34. kg)
Coverage: 1 square
Width: 39³/₈" (1 m)
Length: 33' (10 m)
Rolls/Pallet: 28 PDX/SG

Sand Parting Agent
Both Sides

605 - Panoply Modified Base

Meets or is listed with:

ASTM D 4601, Type II
ASTM E 108-Intertek/WHI Mark-Used in Class 'A', 'B'
and 'C' Fire Listings, FM Approved

Appr. Wt./Roll: 100 lbs. (45.4 kg)
Coverage: 2 square
Width: 39³/₈" (1 m)
Length: 66' (20.1 m)
Rolls/Pallet: 20 PDX/SG

Sand Parting Agent
Both Sides

1000 - ESHAvent[®]

Meets or is listed with:

ASTM E 108-Intertek/WHI Mark-Used in Class 'A', 'B'
and 'C' Fire Listings, FM Approved

Appr. Wt./Roll: 75 lbs. (34. kg)
Coverage: 1.5 square
Width: 39³/₈" (1 m)
Length: 49.2' (15 m)
Rolls/Pallet: 25 PDX/SG

Sand Parting
Agent, Top;
Release Sheet,
Bottom

SBS Modified Cap Sheets

PRODUCT DESCRIPTION & TESTING INFORMATION	SPECIFICATIONS	COLORS
350 GR Premium SBS Modified Mineral Surfaced Fiberglass Cap Sheet <i>Meets or is listed with:</i> ASTM D 3909; ASTM E 108-Intertek/WHI Mark-Used in Class 'A' 'B' and 'C' Fire Rating, UL 790 Classified in Class 'A' Fire Construction	Appr. Wt./Roll: 78 lbs. (35.4 kg) Coverage: 1 square Width: 39 ³ / ₈ " (1 m) Length: 33' (10 m) Rolls/Pallet: 25 PDX 30 SG	Antique Brown Red Black Oak Sienna Blend Dove White Silverwood Midnight Black Storm Grey Natural Wood Weathered Wood Oxford Grey Rainforest
601 - Cap <i>Meets or is listed with:</i> ASTM D 3909; ASTM E 108-Intertek/WHI Mark-Used in Class 'A' 'B' and 'C' Fire Rating, UL 790 Classified in Class 'A' Fire Construction FM Approved	Appr. Wt./Roll: 100 lbs. (45.4 kg) Coverage: 1 square Width: 39 ³ / ₈ " (1 m) Length: 34' (10.3 m) Rolls/Pallet: 20 or 25 PDX, 25 SG	Dove White Midnight Black Tan
625 - Paragon Cap <i>Meets or is listed with:</i> ASTM E 108-Intertek/WHI Mark-Used in Class 'A' 'B' and 'C' Fire Rating, FM Approved, ASTM D 6163 Type I	Appr. Wt./Roll: 102 lbs. (46.3 kg) Coverage: 1 square Width: 39 ³ / ₈ " (1 m) Length: 34' (10.4 m) Rolls/Pallet: 20 PDX/SG	Dove White Midnight Black
650 - Panoply Cap <i>Meets or is listed with:</i> ASTM E 108-Intertek/WHI Mark-Used in Class 'A' 'B' and 'C' Fire Rating, FM Approved, ASTM D 6163 Type II	Appr. Wt./Roll: 76 lbs. (34.5 kg) Coverage: 0.75 square Width: 39 ³ / ₈ " (1 m) Length: 26' (7.9 m) Rolls/Pallet: 25 PDX/SG	Dove White Midnight Black
1020 - ESHalum <i>Meets or is listed with:</i> ASTM E 108-Intertek/WHI Mark-Used in Class 'A' 'B' and 'C' Fire Rating, FM Approved	Appr. Wt./Roll: 97 lbs. (44.0 kg) Coverage: 1 square Width: 39" (1 m) Length: 33' (10 m) Rolls/Pallet: 25 PDX/SG	Aluminum Foil Surface Torch Applied Burn-off Sheet on back

OmniSeal Self Adhered Residential System

PRODUCT DESCRIPTION & TESTING INFORMATION	SPECIFICATIONS	SURFACING
Omni Base - 410 <i>Meets or is listed with:</i> ASTM D 4601, Type II, ASTM E 108-Intertek/WHI Mark- Used in Class 'C' Fire Ratings	Nom. Wt./Roll: 80 lbs. (36.3 kg) Coverage: 2 squares Width: 39 ³ / ₈ " (1 m) Length: 66' (20.1 m) Rolls/Pallet: 25 PDX/SG	<i>Smooth Surfaced</i> <i>Nailable Base</i>
Omni Ply - 420 <i>Meets or is listed with:</i> ASTM E 108-Intertek/WHI Mark-Used in Class 'C' Fire Ratings	Nom. Wt./Roll: 80 lbs. (36.3 kg) Coverage: 2 squares Width: 39 ³ / ₈ " (1 m) Length: 66' (20.1 m) Rolls/Pallet: 20 PDX/SG	<i>Smooth Surfaced</i> <i>Self Adhered Ply</i> <i>Sheet</i>
Omni Cap - 430 <i>Meets or is listed with:</i> ASTM E 108-Intertek/WHI Mark-Used in Class 'B' and 'C' Fire Ratings	Nom. Wt./Roll: 78 lbs. (35.3 kg) Coverage: 1 square Width: 39 ³ / ₈ " (1 m) Length: 34' (10.4 m) Rolls/Pallet: 20 PDX/SG	<i>Granular Cap Sheet</i> Antique Brown Dove White Midnight Black Oxford Grey Sienna Blend Terra Cotta Weathered Wood

APP Modified Sheets

PRODUCT DESCRIPTION & TESTING INFORMATION	SPECIFICATIONS	SURFACING
159 - APP <i>Meets or is listed with:</i> ASTM D 6509, ASTM E 108-Intertek/WHI Mark-Used in Class 'A' 'B' and 'C' Fire Ratings, UL 790 Classified in Class 'A', 'B', and 'C' Fire Construction	Nom. Wt./Roll: 90 lbs. (40.9 kg) Coverage: 2 square Width: 39 ³ / ₈ " (1 m) Length: 65.3' (19.91 m) Rolls/Pallet: 20 PDX/SG	Smooth Surfaced Product
160 - APP <i>Meets or is listed with:</i> ASTM D 6222, ASTM E 108-Intertek/WHI Mark-Used in Class 'A' 'B' and 'C' Fire Ratings, UL 790 Classified in Class 'A', 'B', and 'C' Fire Construction, FM Approved	Nom. Wt./Roll: 90 lbs. (40.9 kg) Coverage: 1 square Width: 39 ³ / ₈ " (1 m) Length: 32.8' (10 m) Rolls/Pallet: 23 PDX/SG	Smooth Surfaced Product
161 - APP <i>Meets or is listed with:</i> ASTM D 6222, ASTM E 108-Intertek/WHI Mark-Used in Class 'A' 'B' and 'C' Fire Ratings, UL 790 Classified in Class 'A', 'B', and 'C' Fire Construction	Nom. Wt./Roll: 105 lbs. (47.7 kg) Coverage: 1 square Width: 39 ³ / ₈ " (1 m) Length: 32.8' (10 m) Rolls/Pallet: 20 PDX/SG	White Tan <i>(Other colors available on request)</i>
162 - APP <i>Meets or is listed with:</i> ASTM D 6222, ASTM E 108-Intertek/WHI Mark-Used in Class 'A' 'B' and 'C' Fire Ratings, UL 790 Classified in Class 'A', 'B', and 'C' Fire Construction, FM Approved	Nom. Wt./Roll: 105 lbs. (47.7 kg) Coverage: 1 square Width: 39 ³ / ₈ " (1 m) Length: 32.8' (10 m) Rolls/Pallet: 20 PDX/SG	White Tan <i>(Other colors available on request)</i>

Walk Board

PRODUCT DESCRIPTION AND SPECIFICATIONS

COLORS

140 - Recycled Rubber Walkboard Pads

Black

Dimensions: 36" x 48" (0.91 m x 1.22 m)
 Appr. Wt.: 3 lbs./sq. ft., 36 lbs./pad (4.46 kg/m²; 16.33 kg/pad)
 Thickness: 1/2" (12.7 mm)
 Pads per Pallet: 100 PDX/SG

141 - Recycled Rubber Walkboard Pads

Black

Dimensions: 32" x 36" (0.81 m x 0.91 m)
 Appr. Wt.: 2 lbs./sq. ft., 16 lbs./pad (4.46 kg/m²; 7.26 kg/pad)
 Thickness: 3/8" (9.5 mm)
 Pads per Pallet: 100 PDX/SG

Roofing Asphalt

For hot application of built-up roofing and waterproofing

PRODUCT DESCRIPTION AND SPECIFICATIONS

SOFTENING POINT

950 - SEBS Mopping Asphalt

205°F ± 5°F
 96°C ± 4°C

Wt./Carton: 50 lbs. (22.7 kg)
 Carton/Pallet: 48 PDX/SG
 Complies with: ASTM 6152

Roof Coatings & Plastic Cements - Asbestos Free

PRODUCT DESCRIPTION AND SPECIFICATIONS

COLORS

703 - Plastic Roof Cement

Black

Consistency: Trowel grade
 Weight: 9 lbs./gal. (1.1 kg/L)
 Maximum VOC: 250 g./lt. (2.07 lbs./gal.) max
 Packaging: 5 gal. (18.9 L) containers
 Complies with: ASTM D 4586 Type I

705 - Cold Method Adhesive

Black

Coverage: 1.5-2 gal./100 sq. ft.
 Weight: 7.5 lbs./gal. (0.9 kg/L)
 Maximum VOC: 250 g./lt.
 Packaging: 5 gal. (18.9 L) containers
 Complies with: ASTM D 3019 Type III.

Roof Coatings & Plastic Cements - *Continued*

PRODUCT DESCRIPTION AND SPECIFICATIONS	COLOR
<p>707 - Low VOC Asphalt Primer Coverage: .75-1 gal./100 sq. ft. (.4 kg/30 m²) Weight: 8.3 lbs./gal. (14.25 kg/L) Maximum VOC: 350 g./lt. (2.9 lbs./gal.) Packaging: 5 & 55 gal. containers (18.9 & 208.2 L) Complies with: ASTM D 41</p>	Dark brown when wet; dries black
<p>709 - Modified Flashing Cement Consistency: Trowel Grade Weight: 9.6 lbs./gal. (1.2/kg/L) Maximum VOC: 250 g./lt. (2.1 lbs/gal.) Packaging: 5 gal. (18.9 L) container Complies with: ASTM D 6511, 3409 & 4586 Type I</p>	Black
<p>727 - Modified Bitumen Adhesive Coverage: 50 sq. ft./gal. (57.7 m²/L) Weight: 8.5 lbs./gal. (1.0 kg/L) Maximum VOC: 250 g./lt. (2.1 lbs/gal.) Packaging: 5 & 55 gal. containers (18.9 & 208.2 L) Complies with: ASTM 3019 Type III</p>	Black
<p>729 - Aluminum Emulsion Weight: 8.8 lbs./gal. (1.05 kg/L) Maximum VOC: 370 g./lt. (1.31 lbs/gal.) Packaging: 5 & 55 gal. (18.9 & 208.2 L) containers Complies with: ASTM D 1227 Type II Class I</p>	Dark brown when wet, dries to Silver
<p>751 - Fibered Emulsion Weight: 8.8 lbs./gal. (1.05 kg/L) Maximum VOC: none - N/A Packaging: 5 & 55 gal. (18.9 & 208.2 L) containers Complies with: ASTM D 1227 Type II Class I</p>	Dark brown
<p>801 - Acrylic Base Coat Weight: 11.5 lbs./gal. (1.38 kg/L) Packaging: 5 & 55 gal. (18.9 & 208.2 L) containers Complies with: ASTM D 6083</p>	Tinted
<p>802 - Acrylic Finish Coat Weight: 11.5 lbs./gal. (1.38 kg/L) Packaging: 5 & 55 gal. (18.9 & 208.2 L) containers Complies with: ASTM D 6083 CRRC Rated Product ID# 0850-0005</p>	White
<p>824 - RCap Touch Up Weight: 12.0 lbs./gal. (1.44 kg/L) Packaging: 3½ gal. (13.25 L) containers Reflectance ≥ 0.81</p>	White



P.O. Box 17217

Portland, OR

97217-0217

Effective: 03/2010