



TECHNICAL PRODUCT DATA SHEET

# RECYCLED RUBBER WALKBOARD PADS

140

## PRODUCT DESCRIPTION

**Product Use:** Malarkey Roofing Products™ (Malarkey) RECYCLED WALKBOARD (140) is used as walk pad for traffic areas on the roof to protect the roof from traffic; i.e. around the hatch, around rooftop units, and walk ways to the units.

**Composition and Materials:** 140 RECYCLED WALKBOARD is made from recycled rubber (100% of the rubber is recycled, tires and binders).

**Application Standards:** Approval for use on all Malarkey roof systems.

## TECHNICAL DATA

Typical average properties, 3' x 4' pad:

Weight	3 lbs. per square foot, 36 lbs. per pad
Dimensions	3' x 4'
Thickness	1/2"
Color	Black

Electrostatic Propensity - AATCC Test Method: NEG 0.9 KV Maximum Voltage

### Compression & Recovery

Immediate	98.1%
After 24 Hours	99.2%
After 96 Hours	99.7%

## APPLICATION PROCEDURES

Malarkey RECYCLED WALKBOARD(140) may be installed by spot adhering in with a One-Part Polyurethane adhesive; i.e. ChemRex CX-948, Sikaflex-1A or Chem Link M-1. (Adhere 4 corners and one spot in center. Spots of adhesive should be at least silver dollar size). **Do not use asphalt cut-back adhesives.** Contact Malarkey for further details.

## TECHNICAL SERVICES

Malarkey has technical assistance available for all phases and requirements of built-up roof coverings. Contact Malarkey for details at (800) 545-1191 or (503) 283-1191, weekdays 7:00 a.m. to 5:00 p.m. Pacific Time.

## AVAILABILITY

Malarkey 140 RECYCLED WALKBOARD is available throughout North America and Pacific Rim countries. Visit [www.MalarkeyRoofing.com](http://www.MalarkeyRoofing.com) for additional product information and availability.

Effective 12.07 | Supersedes all previously published data.

For most current version, go to [www.MalarkeyRoofing.com](http://www.MalarkeyRoofing.com)