



225 SBS MODIFIED FIBERGLASS HIP & RIDGE SHINGLE

Featuring the Scotchgard™ Algae Resistant Roofing System from 3M™

PRODUCT DESCRIPTION

Product Use: Malarkey Roofing Products™ (Malarkey) 225 SBS Modified Fiberglass Hip & Ridge Shingles are manufactured to meet the needs of a high performance hip and ridge cap for all shingled roofs.

Precautions: 225 shingles require dry storage or plastic-covered storage and protection from the weather until applied. Contact Malarkey for further conditions and instructions.

Composition and Materials: 225 shingles are mineral-surfaced* and made with SBS rubber modified asphalt coating and fire retardant fillers on Malarkey fiberglass mat and a sealdown strip. *(granules feature the Scotchgard™ Algae Resistant Roofing System from 3M™ with a 20-year warranty against staining caused by algae growth).

TECHNICAL DATA

Typical Properties:

Approximate Weight	70 lbs. per bundle (31.8 kg)
Exposure	5-5/8" (142.9 mm)
Dimensions	13-1/4" x 9-7/8" (33.65 cm x 25.08 cm)
Coverage per Bundle	41' 3" lineal feet (12.6 m)
Shingles per Bundle	22 shingles
Pieces per Bundle	88 pieces
Granule Adhesion	0.5 gram loss

APPLICATION PROCEDURES

Shingles should be attached to decking by approved type and length fasteners that comply with manufacturer's printed instructions. Malarkey recommends the use of nails for fastening. For specific installation instructions consult Malarkey.

TECHNICAL SERVICES

Malarkey has technical assistance available. Contact Malarkey for details at (800) 545-1191 or (503) 283-1191; Weekdays 7:00 a.m. to 5:00 p.m. Pacific Time.

AVAILABILITY

Malarkey 225 shingles are available throughout North America and Pacific Rim countries. Visit www.MalarkeyRoofing.com for additional product information and availability.

3M™ & Scotchgard™ are trademarks of 3M

Effective 10.09 | Supersedes all previously published data.

For most current version, go to www.MalarkeyRoofing.com