



TECHNICAL PRODUCT DATA SHEET
751 FIBERED EMULSION

PRODUCT DESCRIPTION

Product Use: Malarkey Roofing Products™ (Malarkey) 751 Fibered Emulsion is a black asphalt coating of smooth, thick and creamy consistency in a water emulsion form for use in dampproofing exterior foundation walls and masonry, and as a protective coating for asphalt roofing and metal. The complete absence of solvents makes it a desirable product for use in confined work areas and in areas of potential safety hazards. Complies with ASTM D 1227-95 Type II, Class I.

TECHNICAL DATA

Base	Asphalt, non-asbestos fibers, bentonite, clay and water
Color	Dark brown when wet; dries black
Consistency	Roller or spray grade
Weight Per Gallon	Approximately 9 lbs. (4.26 Kg)
Solids Content	Approximately 50%
Flammability	Non-flammable while wet
Coverage	3 gallons per square (11.4 L)
Container Sizes	5 gallon (18.9 L) 55 gallon (208.2 L)

APPLICATION PROCEDURE

Surfaces to be coated should be clean and free of dust, dirt, scale or anything that might hinder proper adhesion. In hot weather. Extremely dry and porous surfaces should be dampened with water prior to coating. Apply at temperatures above 45° F with a brush, roller or high pressure spray without thinning or heating. Coverage should be 2-3 gallons on metal, and 3 gallons per 100 square feet on asphalt roofing. Dry time is dependent upon ambient temperature and humidity; 8-24 hours is generally sufficient in good, dry weather.

TECHNICAL SERVICES

Malarkey Roofing Products (Malarkey) has technical assistance available for all phases of built-up roof coverings and requirements. Contact Malarkey for details at (800) 545-1191 or (503) 283-1191; Weekdays 7:00 a.m. to 5:00 p.m. Pacific Time.

AVAILABILITY

Malarkey 751 Fibered Emulsion is available throughout North America and Pacific Rim countries. Visit www.MalarkeyRoofing.com for additional product information and availability.

Effective 12.07 | Supersedes all previously published data.

For most current version, go to www.MalarkeyRoofing.com