



TECHNICAL PRODUCT DATA SHEET

Right Start UDL™ FIBERGLASS SBS UNDERLAYMENT

PRODUCT DESCRIPTION

Product: Malarkey Roofing Products™ (Malarkey) Right Start UDL Fiberglass SBS Underlayment is suitable for use as a water tight underlayment or dry-in sheet for steep slope roofing applications, (slopes of 2 inches or more per foot), i.e. asphalt shingles, roof tile, wood shingles, etc. This quality underlayment sheet may be used over various combustible and non-combustible decks as the initial ply or multiple plies for a specified roof underlayment system.

Precautions: Right Start UDL should be kept on ends prior to installation to prevent rolls from flattening. Roof decks should be sound, dry, smooth, meet necessary local requirements and provide positive drainage. Certain tiles that have minimum contact with the surface of UDL may be prone to sliding. Caution: Sanded surface may present slipping hazard.

Composition and Materials: Right Start UDL is manufactured on an inorganic mat saturated with flux SBS modified asphalt and surfaced with a sand release material.

Application Standards: Approved for use under fire-rated composition roofs. Product maybe left exposed for 30 days. Malarkey recommends at least 4" side laps and adequate fastening for extended time frames or in windy or rainy climates. Cooler and colder temperatures: Allow UDL to warm and relax prior to fastening in place.

TECHNICAL DATA

Typical average properties, 2 square roll:

Weight/square	37.5 lbs. (17.01 Kg)
Weight/roll	75 lbs. (34.0 Kg)
Dimensions	39-3/8" wide x 66' long (1 m x 20.1 m)
Lay lines	2", 4" and 18-3/4" minimum (50.8 mm, 102 mm, 476.2 mm)
Perm Rating ASTM E 96-00	Zero

Complies with the physical requirements of ASTM D 4601-97a, Type II.
Meets or exceeds the performance criteria of ASTM D226 and ASTM D4869.
ICC Approval ESR 1561, AC 165 and State of Florida Approval # FL3614.

APPLICATION PROCEDURES

Malarkey Right Start UDL shall be applied as specified in Malarkey Specification Manual. It may be applied in cold weather. Please follow cold weather application instructions.

WARRANTIES

Malarkey offers a 10-year limited materials warranty. Contact Malarkey for details.

TECHNICAL SERVICES

Malarkey has technical assistance available for asphalt shingle roof covering requirements as well as other possible applications. Contact Malarkey for details at (800) 545-1191 or (503) 283-1191; Weekdays 7:00 a.m. to 5:00 p.m. Pacific Time.

AVAILABILITY

Right Start UDL is available throughout North America and Pacific Rim countries. Visit www.MalarkeyRoofing.com for additional product information and availability.

Effective 06.2008 | Supersedes all previously published data.

For most current version, go to www.MalarkeyRoofing.com