

SECURE START® HT

LIMITED
LIFETIME
WARRANTY
INCLUDED

406 Secure Start® HT

SELF-ADHERING HIGH TEMPERATURE UNDERLAYMENT

- Meets and exceeds ASTM D1970
- ASTM E108 Class A
- UV exposure up to six (6) months
- Limited Lifetime Warranty
- Approved for use with Class A fire-rated, code-compliant shingle roof coverings
- 36" x 67' (0.91 m wide x 20.4 m long)

Secure Start® HT is a self-adhering, high temperature underlayment with superior thermal stability and adhesion properties in a temperature range from 40°F [4.4°C] to 260°F [127°C], making it the right choice for complete roof deck coverage under metal roofing applications.† Its asphalt-based adhesive seals tight to the roof deck and around fasteners to protect against leaks caused by ice dams, extreme temperatures, and wind-driven rain. Secure Start® HT is engineered with multiple layers for strength and durability, has a silicone-treated split-release film for ease of installation, and features an anti-skid, walkable surface for roofer safety.

Secure Start® HT can also be used under asphalt shingles, wood shakes and shingles, and mechanically-fastened roof tile. Secure Start® HT joins other quality Malarkey products as part of the Secure Choice™ roof system.

Secure Start® HT underlayment is self-adhering and engineered for performance in high temperatures.

 **Malarkey**
Roofing Products®

P.O. Box 17217, Portland, OR 97217
503.283.1191 | 800.545.1191 | Fax: 503.289.7644
WWW.MALARKEYROOFING.COM

†Check with metal panel manufacturer for approval prior to installation.

Rev. 03/21