


TECHNICAL DETAILS

WIDTH ± 1/8" 13 1/4" 337 mm	LENGTH ± 1/4" 39" 0.99 m
EXPOSURE 5 5/8" 143 mm	GRANULE ADHESION 0.35 g Typical Results
SHINGLES/SQUARE 66 3 bundles/square	SQUARES/PALLET 16

NEX[®] POLYMER MODIFIED ALGAE-RESISTANT, LAMINATED ARCHITECTURAL SHINGLES



TEST COMPLIANCE

ASTM D7158 Class H	ASTM D3462
ASTM D3161 Class F	ASTM D3018 Type I
ASTM E108 Class A Fire Rating	CSA A123.5
ICC-ES ACCEPTANCE AC438	ICC APPROVAL ESR-3150
UL RATING 2218 Class 2	FBC APPROVAL #14809
	

PRODUCT USE

242 Highlander[®] NEX[®] AR is a laminated, algae-resistant asphalt shingle fortified with sustainable NEX[®] polymer modified asphalt technology for enhanced granule adhesion and increased weather protection. Highlander[®] NEX[®] AR features the exclusive nailing accuracy-enhancing design of The Zone[®], a larger nailing area that dramatically improves correct fastener placement. Please consult Malarkey's Technical Services Department for approval of roof systems.

COMPOSITION & MATERIALS

Highlander[®] NEX[®] AR is manufactured on a non-woven fiberglass mat and coated on both sides with NEX[®] polymer modified bitumen (asphalt) that is compounded with a fire-retardant mineral stabilizer. Its surface incorporates an innovative combination of ceramic granules that provide varied color, weatherability, algae protection, even smog reduction.

APPLICATION

Shingles should be applied over a Malarkey underlayment or an approved, code-compliant substitute. Installation instructions, in three languages, are available on the shingle wrapper by scanning the corresponding Quick Response (QR) code, on our website at WWW.MALARKEYROOFING.COM, or by contacting your local Malarkey representative. Industry standards are found in NRCA manuals. Shingles should be attached to decking with approved fasteners, and Malarkey recommends the use of corrosion-resistant nails for this purpose. Staples are not allowed.

PRECAUTION

For best results, Malarkey recommends Highlander[®] NEX[®] AR be protected from the weather and stored in a cool, dry, well-ventilated area until applied. Do not double-stack pallets. Do not use on roofs where the slope is less than 2:12 (2" [51 mm] per 12" [305 mm]). For slopes 2:12 up to 4:12 (4" [102 mm] per 12" [305 mm]), a double layer of underlayment is required (IBC & IRC have an exception for a single layer of ASTM D1970 underlayment in lieu of a double layer). Highlander[®] NEX[®] AR has a factory-applied self-sealing strip that activates in warm weather. When applied in cold weather or windy locations, hand-sealing is recommended but not required if sealant activates. On slopes greater than 21" (533 mm) per 12" (305 mm), hand-sealing underneath and six nails are required. Contact Malarkey for further conditions and instructions.

WARRANTY

Malarkey Roofing Products[®] offers various warranties to meet specific requirements. The warranty packages available for Highlander[®] NEX[®] AR include a Limited Lifetime Warranty, a 110 mph (177 kph) Limited Wind Warranty, and can be combined with other Malarkey products for a 130 mph (209 kph) Enhanced Wind Warranty. Highlander[®] NEX[®] AR also features a 10-year Algae Resistant System Warranty from Malarkey. Contact your roofer, local distribution center, or Malarkey for full details. See below for TECHNICAL ASSISTANCE contact information.

Highlander[®] NEX[®] AR and other Malarkey products are available throughout North America and Pacific Rim countries.

Visit WWW.MALARKEYROOFING.COM for additional product information and availability.

Note: Malarkey Roofing Products[®] Inventory SKU numbers for this product: 242 Highlander[®] NEX[®] AR

FEATURES & BENEFITS

- Sustainable NEX[®] asphalt technology
- Exceptional all-weather performance
- 3M™ Smog-Reducing Granules
- Larger nailing area of The Zone[®]
- Double rain seal protection
- Algae Resistant System Warranty
- Limited Lifetime Shingle Warranty
- Limited & Enhanced Wind Warranties



TECHNICAL ASSISTANCE:

Malarkey has technical services assistance available.
Contact Malarkey for details:
Call weekdays 7:00 am to 5:00 pm Pacific Time
at 800.545.1191 or 503.283.1191.
technicalinquiries@malarkeyroofing.com

CORPORATE OFFICE:

3131 N. Columbia Blvd. Telephone: 503.283.1191
Portland, OR 97217-7472 or 800.545.1191
P.O. Box 17217 Fax: 503.289.7644
Portland, OR 97217-0217

Effective 1/21
Supersedes all previously published data
Check for most current version
on our website.