




TECHNICAL DETAILS

WEIGHT/SQUARE 275 lbs. 124.8 kg	EXPOSURE 5 ⁵ / ₈ " 142.9 mm
SHINGLES/SQUARE 64 4 bundles/square	GRANULE ADHESION 0.35 g Typical Results
WIDTH ± 1/8" 13 ¹ / ₄ " 337 mm	LENGTH ± 1/4" 40" 1.02 m
SQUARES/PALLET 12	

TEST COMPLIANCE

ASTM D7158 Class H	ASTM D3462
ASTM D3161 Class F	ASTM D3018 Type I
ASTM E108 Class A Fire Rating	UL RATING 2218 Class 4
CSA A123.5	ICC APPROVAL ESR-3150
FBC APPROVAL #14809	
	
CEC Title 24, Part 6 Compliant	

See page 2 for solar reflectance technical data.

FEATURES & BENEFITS

- Solar Reflective Shingles
- Scotchgard™ Protection from 3M
- Extreme Weather Protection
- Superior Granular Embedment
- Flexor™ SBS Polymer Modified Asphalt
- The Zone® Nailing Area
- All-Weather Flexibility
- Double Rain Seal Protection
- Limited Lifetime Shingle Warranty
- Limited & Enhanced Wind Warranties

FLEXOR™ SBS POLYMER MODIFIED LAMINATED SOLAR REFLECTIVE SHINGLES



PRODUCT USE

Ecoasis™ Premium is a solar reflective, laminated asphalt shingle used whenever increased flexibility, architectural design, tensile strength, and tear-resistance in shingles is desired. It is fortified with Flexor™ SBS polymer modified asphalt technology for extreme weather protection and includes the Scotchgard™ Algae Resistant Shingle Protector warranty from 3M. Ecoasis™ Premium features the exclusive nailing accuracy-enhancing design of The Zone®. The larger nailing area of The Zone® dramatically improves correct fastener placement. Ecoasis™ Premium shingles meet the required reflectance to be designated with some of the industry's leading energy conservation standards: ENERGY STAR, CRRC listing, and California Energy Code Title 24, Part 6 compliance. Please consult Malarkey's Technical Services Department for approval of roof systems.

COMPOSITION & MATERIALS

Ecoasis™ Premium is manufactured on a woven fiberglass mat and impregnated on both sides with Flexor™ SBS polymer modified asphalt that is compounded with a fire-retardant mineral stabilizer. Ecoasis™ Premium is surfaced with embedded, Scotchgard™ algae resistant granules.

APPLICATION

Shingles should be applied over a Malarkey underlayment or an approved, code-compliant substitute. Installation instructions are available on the shingle wrapper, at WWW.MALARKEYROOFING.COM, or by contacting your local Malarkey representative. Industry standards are found in NRCA manuals. Shingles should be attached to decking with approved fasteners, and Malarkey recommends the use of corrosion-resistant nails for this purpose. Staples are not allowed.

PRECAUTION

For best results, Malarkey recommends Ecoasis™ Premium be protected from the weather and stored in a cool, dry, well-ventilated area until applied. Do not double-stack pallets. Do not use on roofs where the slope is less than 2:12 (2" [51 mm] per 12" [305 mm]). For slopes 2:12 up to 4:12 (4" [102 mm] per 12" [305 mm]), additional deck protection is required. Ecoasis™ Premium has a factory-applied self-sealing strip that activates in warm weather. When applied in cold weather or windy locations, hand-sealing is recommended but not required if sealant activates. In high wind areas and on slopes greater than 12" (305 mm) per 12" (305 mm), hand-sealing underneath and six nails are required. Contact Malarkey for further conditions and instructions.

WARRANTY

Malarkey Roofing Products® offers various warranties to meet specific requirements. The warranty packages available for Ecoasis™ Premium include a Limited Lifetime Warranty, a 110 mph (177 kph) Limited Wind Warranty, and can be combined with other Malarkey products for a 130 mph (209 kph) Enhanced Wind Warranty. Ecoasis™ Premium also carries a 20-year Scotchgard™ warranty against algae growth. Contact your roofer, local distribution center, or Malarkey for full details. See below for TECHNICAL ASSISTANCE contact information.

Ecoasis™ Premium and other Malarkey products are available throughout North America and Pacific Rim countries.

Visit WWW.MALARKEYROOFING.COM for additional product information and availability.

Note: Malarkey Roofing Products® (Malarkey) Inventory SKU number for this product: 283 Ecoasis™ Premium featuring the Scotchgard™ Algae Resistant Shingle Protector from 3M

TECHNICAL ASSISTANCE:

Malarkey has technical services assistance available. Contact Malarkey for details: Call weekdays 7:00 am to 5:00 pm PST, at 800.545.1191 or 503.283.1191. technicalinquiries@malarkeyroofing.com

CORPORATE OFFICE:

3131 N. Columbia Blvd. Telephone: 503.283.1191
Portland, OR 97217-7472 or 800.545.1191
P.O. Box 17217 Fax: 503.289.7644
Portland, OR 97217-0217



**FLEXOR™ SBS POLYMER MODIFIED
SOLAR REFLECTIVE SHINGLES**

SOLAR REFLECTANCE TECHNICAL DATA

Ecoasis™ Premium is listed with the Cool Roof Rating Council. Ecoasis™ Premium has tested to these radiative property values:



Cool Roof Rating Council ratings are determined for a fixed set of conditions, and may not be appropriate for determining seasonal energy performance. The actual effect of solar reflectance and thermal emittance on building performance may vary.

Manufacturer of product stipulates that these ratings were determined in accordance with the applicable Cool Roof Rating Council procedures.

	ECOASIS™ PREMIUM (AGAVE)		ECOASIS™ PREMIUM (MESQUITE)		ECOASIS™ PREMIUM (TUMBLEWEED)	
	INITIAL	WEATHERED	INITIAL	WEATHERED	INITIAL	WEATHERED
SOLAR REFLECTANCE	0.27	0.25	0.28	0.26	0.26	0.26
THERMAL EMITTANCE	0.92	0.96	0.93	0.97	0.93	0.94
SOLAR REFLECTIVE INDEX (SRI)	29	28	31	30	28	28
Related Product ID Licensed Manufacturer ID: 0850 Classification: Production Line	0850-0020		0850-0018		0850-0019	



Energy Star is only recognized in the U.S., not in Canada.

TECHNICAL ASSISTANCE:

Malarkey has technical services assistance available.
Contact Malarkey for details:
Call weekdays 7:00 am to 5:00 pm PST,
at 800.545.1191 or 503.283.1191.
technicalinquiries@malarkeyroofing.com

CORPORATE OFFICE:

3131 N. Columbia Blvd. Telephone: 503.283.1191
Portland, OR 97217-7472 or 800.545.1191
P.O. Box 17217 Fax: 503.289.7644
Portland, OR 97217-0217