



# SAFETY DATA SHEET

## 1 PRODUCT AND COMPANY IDENTIFICATION

**Product Type:** Malarkey NEX® SBS Polymer Modified Asphalt Fiberglass Shingles

**Trade Names/SKU Numbers:**

**241 Highlander® laminate shingles**

**242 Highlander® AR laminate shingles**

**245 Highlander® Cool laminate shingles**

**Manufacturer:**

Malarkey Roofing Products®

P.O. Box 17217

3131 N. Columbia Blvd.

Portland, OR 97217

Phone: 503-283-1191

[www.malarkeyroofing.com](http://www.malarkeyroofing.com)

**Use:** Steep slope roofing shingles

**Emergency Contact:**

CHEMTREC®: 1-800-262-8200 (24 HOUR)

## 2 HAZARD(S) IDENTIFICATION

**Signal Word:** WARNING

**Carcinogenicity:** Category 2A

**Skin Irritation:** Category 2

### HAZARD STATEMENTS

- Causes skin and eye irritation.
- May cause an allergic skin reaction.
- Causes damage to organs through prolonged or repeated exposure.

### PRECAUTIONARY STATEMENTS

- Read instructions before use.
- Use in a well-ventilated area.
- Do not handle until all safety precautions have been read and understood.
- Do not breathe dust.
- Wear proper *Personal Protective Equipment* including gloves/protective clothing/eye protection/face protection, and respirator where appropriate.
- Do not eat, drink or smoke when using this product.
- Thoroughly wash hands and exposed skin after handling.

### GHS CLASSIFICATION



### 3 COMPOSITION / INFORMATION ON INGREDIENTS

| Ingredients                      | CAS #      | Ingredient % |
|----------------------------------|------------|--------------|
| Asphalt                          | 8052-42-4  | 15 - 30      |
| Limestone                        | 1317-65-3  | 30 - 40      |
| Fiberglass Mat                   |            |              |
| Fiberglass                       | 65997-17-3 | 0 - 5        |
| Urea Formaldehyde Binder         | 9011-05-6  | 0 - 0.003    |
| Formaldehyde (gas)               | 50-00-0    | < 0.04       |
| SBS                              | 9003-55-6  | 3 - 12       |
| Carbon Black                     | 133-86-4   | < 2%         |
| Naphthenic Oil                   | 64742-04-7 | < 2%         |
| Zinc dust                        | 1314-12-2  | trace        |
| Backing Sand, Crystalline Silica | 14808-60-7 | 0 - 6        |
| Mineral Granules                 | Mixture    | 25 - 35      |

### 4 FIRST-AID MEASURES

**Eye contact:** Immediately flush eyes with plenty of cool water for at least 20 minutes, occasionally lifting the eye lids to ensure thorough rinsing. Get medical attention if irritation persists.

**Skin contact:** Clean any exposed skin with warm soapy water if possible. If not, and a waterless hand cleaner is used, it should be without pumice. Do not use solvents or thinners to remove material from skin. Get medical attention if irritation persists or develops.

**Ingestion:** If swallowed, do not induce vomiting. If vomiting occurs, keep head lower than hips to avoid aspiration of vomit into the lungs which can cause inflammation or pneumonitis. Call poison control center or get immediate medical attention.

**Inhalation:** If inhalation of dust occurs, remove person to fresh air. Drink water to clear throat or blow nose to clear. If not breathing, give artificial respiration or give oxygen by trained personnel and get immediate medical attention.

**Notes to physician:** Treatment should be based on removing the source of irritation with treatment of symptoms as necessary.

### 5 FIRE-FIGHTING MEASURES

**Flash point:** 525°F minimum (274°C), Cleveland Open Cup

**Auto-ignition temperature:** >650°F

**Extinguishing media:** Dry chemical, CO<sub>2</sub>, or foam fire extinguisher should be used for controlling small fires. Avoid use of straight-stream water.

**Special firefighting procedures:** Avoid breathing fumes. Firefighters should wear NIOSH approved positive pressure breathing apparatus (SCBA) with full face mask and full protective equipment.

**Unusual fire or explosion hazards:** When heated, fumes may burn if ignition source is provided. Petroleum asphalt fumes can explode if emitted in an enclosed environment and supplied with an ignition source. Burning product will cause thick black smoke.

**Hazardous combustion products:** Carbon monoxide, carbon dioxide, ozone, hydrogen sulfide, oxides of sulfur and various hydrocarbons during heating or burning. These combustion products are not expected unless product is heated or burned.

## 6 ACCIDENTAL RELEASE MEASURES

**Precautions if material is spilled or released:** Pick up large pieces. Leather or cotton gloves must be worn when handling. Do not dry sweep dusts or blow with compressed air. Wet sweep only.

**Waste disposal methods:** It is highly recommended that this product be recycled. Otherwise, dispose in accordance with applicable Federal, State, and Local regulations. Do not burn.

## 7 HANDLING AND STORAGE

**Storage temperature:** Store away from heat and all ignition sources and open flames in accordance with applicable laws and regulations. Product should not be burned or heated using a direct flame.

**Precautions to be taken in handling and storage:** Follow recommended work practices and use recommended personal protective clothing and equipment.

## 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

| Components                       | CAS #      | OSHA                                 |       | ACGIH                                |                     |
|----------------------------------|------------|--------------------------------------|-------|--------------------------------------|---------------------|
|                                  |            | TWA                                  | STEL  | TWA                                  | STEL                |
| Asphalt                          | 8052-42-4  | NE                                   | NE    | 0.5 mg/m <sup>3</sup> <sup>a</sup>   | NE                  |
| Limestone                        | 1317-65-3  | 15 / 5 <sup>b</sup>                  | NE    | 10 / 3 <sup>b</sup>                  | NE                  |
| Fiberglass                       | 65997-17-3 | 15 / 5 <sup>b</sup>                  | NE    | 5 <sup>b</sup>                       | NE                  |
| Urea Formaldehyde Binder         | 9011-05-6  | NE                                   | NE    | NE                                   | NE                  |
| Formaldehyde (gas)               | 50-00-0    | 0.75 ppm                             | 2 ppm | NE                                   | 0.3 ppm             |
| Styrene Butadiene Copolymer      | 9003-55-6  | NE                                   | NE    | NE                                   | NE                  |
| Carbon Black                     | 133-86-4   | 3.5 mg/m <sup>3</sup>                | NE    | NE                                   | NE                  |
| Naphthenic Oil                   | 64742-04-7 | NE                                   | NE    | 5 mg/m <sup>3</sup>                  | NE                  |
| Zinc dust                        | 1314-12-2  | 10 mg/m <sup>3</sup> <sup>b</sup>    | NE    | 10 mg/m <sup>3</sup> <sup>b</sup>    | 5 mg/m <sup>3</sup> |
| Backing Sand, Crystalline Silica | 14808-60-7 | 0.025 mg/m <sup>3</sup> <sup>c</sup> | NE    | 0.025 mg/m <sup>3</sup> <sup>c</sup> | NE                  |

NE = Not Established

<sup>a</sup> = Asphalt Fume as benzene-soluble inhalable aerosol

<sup>b</sup> = Total Nuisance Dust / Respirable Dust (mg/m<sup>3</sup>)

<sup>c</sup> = Crystalline Silica TWAs for respirable fraction

**Respiratory protection:** Normally not needed in well-ventilated areas unless cutting with power tools. If applicable exposure standards are exceeded or can be exceeded introduce ventilation to remove dust. If increased ventilation is not possible, use a NIOSH approved air-purifying respirator. If concentrations are sufficiently high that this respirator is inadequate, or high enough to cause oxygen deficiency, use a

positive pressure self-contained breathing apparatus (SCBA). Follow all applicable respirator/SCBA use, fitting, and training standards and regulations.

**Ventilation:** Use only with adequate ventilation to maintain exposures below applicable exposure limits.

**Eye protection:** Safety glasses with side shields must be used when handling.

**Skin protection:** Must wear leather or cotton gloves during application and tear-off activities.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

**Appearance and odor:** Solid material with granular surfacing, sand backing, very low odor.

**Odor threshold:** Not Applicable

**Vapor pressure:** Not Applicable

**pH:** Not Applicable

**Specific gravity/relative density:** >2

**Vapor density (Air = 1):** Not Applicable

**Viscosity:** Not Applicable; solid

**Boiling point:** >700°F

**Melting point:** >200°F

**Solubility (IES):** No data available

**Flash point:** >525°F

**Evaporation rate (Butyl Acetate = 1) :** <0.1

**Flammability (Solid and Gas):** Not Applicable

**Initial boiling point and boiling range:** Not Applicable

**Auto-ignition temperature:** >343°C/680°F

**Upper/lower flammability or explosive limits:** Not Applicable

**Decomposition temperature:** Not Applicable

## 10 STABILITY AND REACTIVITY

**Stability:** Stable

**Reactivity:** Reactivity will not occur.

**Conditions to avoid:** Keep from heat, sparks, open flame and other sources of ignition. Avoid contact with strong oxidizing agents. PRODUCT SHOULD NOT BE BURNED OR HEATED USING A DIRECT FLAME DEVICE.

**Hazardous reaction:** Polymerization will not occur.

**Incompatibility (materials to avoid):** Strong acids or bases, oxidizing agents and selected amines.

**Hazardous combustion products:** Carbon monoxide, carbon dioxide, ozone, hydrogen sulfide, oxides of sulfur and various hydrocarbons during heating or burning. These combustion products are not expected unless product is heated or burned.

## 11 TOXICOLOGICAL INFORMATION

**Eye:** May cause eye irritation.

**Skin:** May cause skin irritation.

**Inhalation:** Dust may cause upper respiratory irritation.

**Ingestion:** May cause harmful effects if swallowed.

### THE FOLLOWING COMPONENT DATA IS PROVIDED FOR USER INFORMATION:

#### SILICA

**Cancer:** This product contains crystalline silica (quartz). IARC has determined that crystalline silica inhaled in the form of quartz from occupational sources is carcinogenic to humans (Group 1). IARC concluded that there was sufficient evidence in humans and animals for the carcinogenicity of inhaled crystalline silica in the form of quartz from occupational sources. The NTP has classified silica as known to be a human carcinogen. The physical nature of this product may help limit any inhalation hazard from

crystalline silica during application and in its hardened state. However, physical forces such as grinding, drilling and other demolition work on this product may liberate crystalline silica dust.

**Acute effects:** Exposure to silica dust can cause irritation of the eyes, nose and throat. Exposure to high concentrations can also cause Accelerated Silicosis causing progressive shortness of breath, fever, coughing, and weight loss.

**Chronic effects:** In addition to cancer, breathing of silica over a period of time can cause damage to the lung tissue and silicosis after long exposure at low concentrations causing shortness of breath, fever, coughing, and weight loss. Prolonged and repeated exposure to respirable silica-containing dust may also cause autoimmune disease, kidney disease, tuberculosis, nonmalignant respiratory disease, and bronchitis.

## FORMALDEHYDE

**Cancer:** This product may contain extremely low levels of formaldehyde that are not expected to cause a health hazard under normal conditions of use. IARC and NTP have classified formaldehyde as a human carcinogen based on sufficient evidence that formaldehyde causes nasopharyngeal cancer in humans, limited evidence for cancer of the nasal cavity and paranasal sinuses, and "strong but not sufficient evidence" for leukemia. The finding for leukemia reflects the epidemiologists' finding of strong evidence in human studies coupled with an inability to identify a mechanism for induction of leukemia. The physical nature of this product may help limit any inhalation hazard from formaldehyde during application and in its hardened state.

**Acute effects:** The major acute toxic effects caused by formaldehyde exposure via inhalation are eye, nose, and throat irritation and effects on the nasal cavity. Other effects seen from exposure to high levels of formaldehyde in humans are coughing, wheezing, chest pains, and bronchitis. Ingestion exposure to formaldehyde in humans has resulted in corrosion of the gastrointestinal tract and inflammation and ulceration of the mouth, esophagus, and stomach.

**Chronic effects:** In addition to cancer, exposure to formaldehyde by inhalation in humans has been associated with respiratory symptoms and eye, nose, and throat irritation. Repeated contact with liquid solutions of formaldehyde has resulted in skin irritation and allergic contact dermatitis in humans.

## 12 ECOLOGICAL INFORMATION

**Ecotoxicity:** No data available.

**Persistence and degradability:** No data available.

**Bioaccumulative potential:** No data available.

**Mobility in soil:** No data available.

**Other adverse effects (GHG, Ozone):** No data available.

## 13 DISPOSAL CONSIDERATIONS

This product has not been regulated as a hazardous waste by the USEPA. Recycling is recommended. Otherwise, dispose in accordance with Federal, State, and Local regulations. Do not burn. Do not dispose as sewage.

## 14 TRANSPORT INFORMATION

This product is not regulated as a hazardous material for transport under 49 CFR or for vessel transport under the IMDG Code.

**UN number:** Not applicable

**UN proper shipping name:** Not applicable

**Packing group, if applicable:** Not applicable

**Environmental hazards:** Not applicable

**Transport in bulk:** Not applicable

**Special precautions:** Not applicable

## 15 REGULATORY INFORMATION

**Toxic Substances Control Act (TSCA):** Some components in this product are listed on the TSCA Inventory.

**Comprehensive Environmental Response Compensation and Liability (CERCLA):** None

**Superfund Amendments and Reauthorization Act of 1986 (SARA), Title III, Section 302 Extremely Hazardous Substances:** None

**Section 311/312 Hazard Categories:** Immediate Health; Delayed Health; Fire Hazard

**Section 313 Reportable Ingredients:** This material contains formaldehyde (CAS# 50-00-0), which is subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR Part 373.

**California Proposition 65:** WARNING: This product can expose you to chemicals, including crystalline silica (quartz), bitumen, titanium dioxide, and formaldehyde, which are known to the State of California to cause cancer. For more information go to: [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## 16 OTHER INFORMATION

### HMIS RATING

|                               |
|-------------------------------|
| <b>HEALTH: 1</b>              |
| <b>FLAMMABILITY: 1</b>        |
| <b>REACTIVITY: 0</b>          |
| <b>PERSONAL PROTECTION: B</b> |



### DISCLAIMER

Malarkey Roofing Products® is furnishing this information without warranty, expressed or implied, and it is accurate to the best of our knowledge. The data on this sheet are related only to the specific material designated herein. Malarkey Roofing Products® assumes no legal responsibility for use or reliance upon these data.