



STEEP SLOPE WARRANTY PROGRAM

A TRUE MATERIALS AND LABOR WARRANTY
FOR MALARKEY COMMERCIAL APPROVED APPLICATORS

Malarkey's confidence in its steep slope roofing warranty stems from the integrity of the Commercial Approved Applicators Program and Malarkey's superior product technology. Only the most skilled contractors with a proven track record of quality craftsmanship meet program requirements.

A MALARKEY SHINGLE IS... PERFORMANCE ENGINEERED

Adapts to Weather – NEX® Technology rubberizes shingles to better adapt to varying and extreme weather conditions.

Resists Impact – Synthetic rubber (SBS) polymers add pliability and resilience to resist tears and provide a high level of impact protection (hail, debris). **Class 3 and 4 impact ratings.**

Resists Wind & Rain – Synthetic adhesive (SEBS), double rain seals, and The Zone®, our patented wider nailing area, seal down shingles and block out wind-driven rain.

Resists Fire – Shingles meet highest fire rating (Class A).

ENVIRONMENTALLY DESIGNED

Reduces Smog – 3M™ Smog-Reducing Granules harness sunlight to reduce air pollution.

Upcycles Materials – Recycled rubber and plastics are repurposed to enhance shingle durability.

Lasts Longer – Superior granule adhesion protects shingles from premature aging caused by solar rays.

Cleaner Manufacturing – NEX® Technology results in much lower emissions than the highly-pollutive oxidation process used to make traditional shingles.

Less Waste – Malarkey is the only North American roofing manufacturer to earn GreenCircle® Certification for Waste Diversion from Landfill at all its facilities.

To qualify for the Malarkey Roofing Steep Slope ND L Warranty Program, certain conditions are required.

Highlights of the program:

- Roofing contractor must be a Malarkey Commercial Approved Applicator prior to project bid, the roofing system applied according to Malarkey ND L Warranty installation instructions, and all Malarkey products used where applicable
- Project must be a commercial building, and Warranty Application must be received by Malarkey 2 weeks prior to the start of the project
- Complete tear-off to the roof deck required; re-covers not allowed
- Wood board decks must be completely overlaid with sheathing
- Roof decks properly ventilated
- Eaves and rakes flashed with perimeter metal drip edge
- Slopes between 2 and 5 inches per foot require a double layer of underlayment and slopes between 2 and 3 inches, an initial layer of self-adhering underlayment
- Nails only for fastening; staples not allowed
- In roof valleys, Arctic Seal® required on the roof deck first
- For open metal valleys, W valley metal must be a minimum of 24" wide
- For complete program conditions, products, and instructions, refer to Malarkey's Additional Installation Requirements for Commercial Approved Applicators Relative to Steep Slope ND L Shingle-Warrantied Projects

Available in 5, 10, 15 and 20-year terms*

All materials used on warrantied projects must be Malarkey Roofing Products® including:

- Vista® shingle line, Ecoasis®, Legacy® shingle line, or Windsor®
- Right Start® UDL, Arctic Seal® self-adhering underlayment or Secure Start® underlayment line
- EZ-Ridge®, EZ-Ridge® XT or RidgeFlex® (10", 12") hip and ridge shingles
- Smart Start® starter shingles or Smart Start® with Windsor® Starter shingles

* Vista® line, and Ecoasis® available in 5, 10, and 15-year terms. For Hawaii, Alaska and other remote locations, there will be additional charges for airfare, car rental, and lodging, when applicable. Most shingle colors offered in the Malarkey Steep Slope Warranty Program are available with Scotchgard™ Protector from 3M.