TECHNICAL BULLETIN

INSTALLATION OF MALARKEY ROOFING PRODUCTS SHINGLES OVER UNVENTED ROOF ASSEMBLIES

Malarkey Roofing Products® installation guidelines state:

"To prevent harmful condensation or heat buildup, air must circulate freely under the roof deck. Install roof vents at ridges and eaves. Ventilation provisions must meet or exceed current FHA or HUD requirements and adopted building codes."

In the section entitled, EXCLUSIONS, Malarkey *warranties* state: "The Limited Lifetime Warranty covers only manufacturing defects in Malarkey shingles that adversely affect the performance of the shingle. The warranty does not cover other products such as flashing and metal work or *damage to shingles attributable in whole or in part to other causes including, but not limited to: "Improper ventilation."* (Many other adverse conditions are listed in this section.)

The warranty against manufacturing defects is in effect — however, if the project is not properly ventilated directly under the sheathing, any problems that occur or damage to the shingles because of the lack of ventilation would not be covered by Malarkey warranties.

Reference Malarkey warranties online at: https://www.malarkeyroofing.com/warranties/.

Contact Malarkey Technical Services with questions at (800) 545-1191 or (503) 283-1191, 7:00 am to 5:00 pm, Pacific Time, or email us at malarkey.technicalinquiries@amrize.com.

rev. 07/26